



NOTES

1. PIVOT PINS ARE FURNISHED WITH CLEVIS MOUNTED CYLINDERS AS STANDARD.
2. PIVOT PINS MUST BE ORDERED AS A SEPARATE ITEM IF TO BE USED WITH SPHERICAL BEARING, ROD EYES AND SPHERICAL BEARING CLEVIS BRACKET..
3. SHEAR CAPACITY (lb.) 53,600.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN. WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

	B				
A	0229297	1/5/18			
-	0168745	9/15/16			
REV.	ECO-	DATE			

MATERIAL
STEEL

HEAT TREATMENT

PARKER HANNIFIN CORP.
CYLINDER DIVISION
DES PLAINES, IL 60016



PIVOT PIN
WITH RETAINING RINGS
Ø 1 1/4" PIN

PART NO. 0977260125	
DRAWING NO. 0977260125_CTLG	REV. B

(UNLESS OTHERWISE SPECIFIED) TOLS. AND FINISHES PER ES-008, GEOMETRIC TOLS. PER CURRENT ASME Y14.5M STANDARD.

SCALE 2:3	DATE 9/15/16	DRAWN BY Parker Hannifin	CHK. BY	APPD. BY
--------------	-----------------	-----------------------------	---------	----------

© COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

Autodesk Inventor A