



NOTES

1. PIVOT PINS ARE FURNISHED WITH CLEVIS MOUNTED CYLINDERS AS STANDARD.
2. PIVOT PINS MUST BE ORDERED AS A SEPARATE ITEM IF TO BE USED WITH SPHERICAL BEARING, ROD EYES AND SPHERICAL BEARING CLEVIS BRACKET.
3. SHEAR CAPACITY (lb.) 137,400.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN. WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

A	0286574	04/19/19
-	0229297	1/5/18
REV.	ECO-	DATE

MATERIAL		
STEEL		
HEAT TREATMENT		

PARKER HANNIFIN CORP.
 CYLINDER DIVISION
 DES PLAINES, IL 60016

(UNLESS OTHERWISE SPECIFIED) TOLS. AND FINISHES PER ES-008, GEOMETRIC TOLS. PER CURRENT ASME Y14.5M STANDARD.
 © COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

SCALE	DATE	DRAWN BY	CHK. BY	APPD. BY
2:5	1/5/18	CP	CP	

PIVOT PIN
 WITH RETAINING RINGS
 Ø 2" PIN

PART NO.	
0977260200_CTLG	
DRAWING NO.	REV.
0977260200_CTLG	A

Autodesk Inventor