



4X Ø.47 THRU

NOTES:
1. LOAD CAPACITY (lb.) 9,425.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

(UNLESS OTHERWISE SPECIFIED) TOLS. AND FINISHES PER ES-008. GEOMETRIC TOLS. PER CURRENT ASME Y14.5M STANDARD.

© COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

MATERIAL			PARKER HANNIFIN CORP.		
1020 / 1018 STEEL			CYLINDER DIVISION		
HEAT TREATMENT			DES PLAINES, IL 60016		
REV.	E.C.NO.	DATE	SCALE	DATE	DRAWN BY
-	0168745	9/15/16	5:4	9/15/16	Parker Hannifin
APPD. BY			CHK. BY		

CLEVIS BRACKET
FOR SE MOUNT $\text{Ø}1"$ PIN

PART NO.		
0977270100		
DRAWING NO.		REV.
0977270100_CTLG		-

B

Autodesk Inventor