



NOTES  
1. MAXIMUM PULL LOAD (lb) 370850.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

PARTS SHOWN AS STANDARD CATALOG DIMENSIONS. ACTUAL PARTS & CAD MODELS MAY VARY PER STANDARD TOLERANCES.  
© COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

1			38994		10/10/10		MATERIAL STEEL	
REV.	E.C.NO.	DATE	HEAT TREATMENT		PARKER HANNIFIN CORP. CYLINDER DIVISION DES PLAINES, IL 60016			
SCALE .25X	DATE 10/10/10	DRAWN BY Parker Hannifin	CHK. BY	APPD. BY	LINEAR ALIGNMENT COUPLER 4 1/4-12 THREAD			

PARTER HANNIFIN CORP.   
CYLINDER DIVISION  
DES PLAINES, IL 60016

PART NO. 1337390425	
DRAWING NO. 1337390425_CTLG	REV. 1

B

Autodesk Inventor