



- NOTES
 1. MAXIMUM PULL LOAD (lb) 2425.
 2. APPROXIMATE WEIGHT (lb) .35

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

PARTS SHOWN AS STANDARD CATALOG DIMENSIONS. ACTUAL PARTS & CAD MODELS MAY VARY PER STANDARD TOLERANCES.
 © COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

1			38994			10/10/10			MATERIAL STEEL		
REV.			E.C.NO.			DATE			HEAT TREATMENT		
SCALE 2X			DATE 10/10/10			DRAWN BY Parker Hannifin			CHK. BY		
									APPD. BY		

PARKER HANNIFIN CORP.
 CYLINDER DIVISION
 DES PLAINES, IL 60016

LINEAR ALIGNMENT COUPLER
 3/8-24 THREAD

PART NO. 1347570038	
DRAWING NO. 1347570038_CTLG	REV. 1

B

Autodesk Inventor