



NOTES

1. PIVOT PINS ARE FURNISHED WITH CLEVIS MOUNTED CYLINDERS AS STANDARD.
2. PIVOT PINS MUST BE ORDERED AS A SEPARATE ITEM IF TO BE USED WITH KNUCKLES, ROD CLEVISES OR CLEVIS BRACKETS.
3. SHEAR CAPACITY (lb.) 199600.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

PARTS SHOWN AS STANDARD CATALOG DIMENSIONS. ACTUAL PARTS & CAD MODELS MAY VARY PER STANDARD TOLERANCES.
 © COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

1			38994		10/10/10		MATERIAL STAINLESS STEEL	
REV.	E.C.NO.	DATE	HEAT TREATMENT		PARKER HANNIFIN CORP. CYLINDER DIVISION DES PLAINES, IL 60016			
SCALE FULL	DATE 10/10/10	DRAWN BY Parker Hannifin	CHK. BY	APPD. BY	PIVOT PIN WITH RETAINING RINGS Ø2.500" PIN STAINLESS STEEL			

PARTER HANNIFIN CORP. 
 DES PLAINES, IL 60016
 PIVOT PIN
 WITH RETAINING RINGS
 Ø2.500" PIN
 STAINLESS STEEL

PART NO. 0938880000	
DRAWING NO. 0938880000_CTLG	REV. 1

B

Autodesk Inventor