



NOTES

1. PIVOT PINS ARE FURNISHED WITH CLEVIS MOUNTED CYLINDERS AS STANDARD.
2. PIVOT PINS MUST BE ORDERED AS A SEPARATE ITEM IF TO BE USED WITH KNUCKLES, ROD CLEVISES OR CLEVIS BRACKETS.
3. SHEAR CAPACITY (lb.) 105200.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

PARTS SHOWN AS STANDARD CATALOG DIMENSIONS. ACTUAL PARTS & CAD MODELS MAY VARY PER STANDARD TOLERANCES.

© COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

1			38994		10/10/10		MATERIAL		STEEL	
REV.			E.C.NO.		DATE		HEAT TREATMENT		PARKER HANNIFIN CORP.	
SCALE			DATE		DRAWN BY		CHK. BY		APPD. BY	
FULL			10/10/10		Parker Hannifin					

PARKER HANNIFIN CORP.
 CYLINDER DIVISION
 DES PLAINES, IL 60016

Parker
 Cylinder

PIVOT PIN
 WITH RETAINING RINGS
 Ø1.750" PIN

PART NO.		0683720000	
DRAWING NO.		0683720000_CTLG	
REV.		1	

B

Autodesk Inventor