



**NOTES**

1. PIVOT PINS ARE FURNISHED WITH CLEVIS MOUNTED CYLINDERS AS STANDARD.
2. PIVOT PINS MUST BE ORDERED AS A SEPARATE ITEM IF TO BE USED WITH KNUCKLES, ROD CLEVISES OR CLEVIS BRACKETS.
3. SHEAR CAPACITY (lb.) 420900.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORPORATION. THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER HANNIFIN, WILL NOT BE USED FOR ANY PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER HANNIFIN, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER HANNIFIN.

PARTS SHOWN AS STANDARD CATALOG DIMENSIONS. ACTUAL PARTS & CAD MODELS MAY VARY PER STANDARD TOLERANCES.

© COPYRIGHT PARKER. ALL RIGHTS RESERVED. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT.

1	38994	10/10/10	MATERIAL STEEL		
REV.	E.C.NO.	DATE	HEAT TREATMENT		
SCALE .75X	DATE 10/10/10	DRAWN BY Parker Hannifin	CHK. BY	APPD. BY	

PARKER HANNIFIN CORP.  
CYLINDER DIVISION  
DES PLAINES, IL 60016

PIVOT PIN  
WITH RETAINING RINGS  
Ø3.500" PIN

PART NO. <b>0735450000</b>	
DRAWING NO. <b>0735450000_CTLG</b>	REV. <b>1</b>

B

Autodesk Inventor